

Acousti-Mat® Tape



Description

Maxxon® Acousti-Mat® Perm-Rated Tape is a heavy-duty, moisture resistant tape designed to seal seams in Acousti-Mat® sound mat installations and to secure Maxxon® Perimeter Isolation Strips to Acousti-Mat sound control mat fabric.

Where to Use

Application

With sound mat installation.

Subfloor

All interior subfloors.

Technical Characteristics

Thickness:	0.08 mm (3 mils)
Roll Width:	3" (72 mm)
Roll Length:	180' (54.86 m)
Material:	Polypropylene fill coated with a synthetic rubber resin adhesive
Tensile Strength:	Longitudinal: 36–42 lbs. / in. width Transverse: 74 lbs. / in. width
Elongation:	150% (ASTM 3759)
Application Temperature Range:	35° F to 110° F
Service Temperature Range:	20° F to 150° F

Features

- Tears easily
- More cost-effective than other options currently used
- Excellent bond
- Moisture resistant with a Perm rating — can be used against walls and in place of Maxxon Moistop in applications against drywall
- Watertight seal

** Physical and performance characteristics shown above are obtained from tests performed according to ASTM and PSTC test methods. Maxxon Corporation can make no warranty of any kind as to the results of the adhesive tape product use. The information published here is representative of laboratory research on these products are believed to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own.*

Revised: 2025-04-30