

AlphaSorb® Paintable Acoustic Panel



Description

Our AlphaSorb® Paintable Acoustic Panel provides a blank canvas in a finish similar to drywall ready to accept any number of paint colors for endless design possibilities. This paintable panel is the best choice for projects requiring a soft white appearance or need to be a specific color.

Constructed with a high density fiberglass core and a high impact facing, these panels offer excellent acoustical performance. Paintable panels are available in sizes or shapes up to four foot by ten foot and may be installed as white panels or be painted on location in any color you desire.



Technical Characteristics

Size:	up to 4' x 10'
Thickness:	1" 2"
Density:	6-7 lb./cu. ft. fiberglass board
Finish:	Paintable Fabric
Edge Detail:	Square Chemically Hardened Edge
Mounting	Impaling Clips Z-clips Rotofast (drywall) or as specified
Fire Rating:	Class 1 or A per ASTM E84
NRC:	0.75 (1") 1.00 (2")

Sound Absorbing Performance

Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1"	0.01	0.24	0.71	0.99	1.06	1.05	0.75
2"	0.30	0.85	1.09	1.05	0.99	1.01	1.00

Revised: 2025-04-30