

Maxxon® Commercial Multi-Use Acrylic Primer



Description

Maxxon® Commercial Multi-Use Acrylic Primer is a multipurpose, high solids liquid polymer used to prime subfloors such as concrete, lightweight concrete and wood, prior to pouring a Maxxon underlayment. It is also used to seal new Maxxon underlayments prior to installing finished floor goods.

Where to Use

Application

Multifamily, light commercial and commercial construction.

Subfloor

Prime - Concrete and wood subfloors.

Seal - Gypsum underlayments..

Features

- Penetrating primer over most subfloors
- Increases bond for Maxxon underlayments
- Can be used as a sealer over Maxxon underlayments prior to applying finished floor goods
- Reduces porosity which allows proper open time for adhesives
- Low odor, low VOC

Technical Characteristics

% Solid	49–51%
Color	White, dries transparent
Coverage	Undiluted - 300 ft ² (27.9 m ²) 1:1 Mix Ratio - 600 ft ² (55.7 m ²) 4:1 Mix Ratio - 1,500 ft ² (139.4 m ²) 6:1 Mix Ratio - 2,100 ft ² (195 m ²)
Packaging	1-gallon (3.8 L) 5-gallon (18.9 L) 55-gallon (208.2 L) 275-gallon (1,041 L)



Revised: 2026-05-04