

# Maxxon® Commercial Profile



## Description

Maxxon® Commercial Profile is a spray-applied, direct-to-concrete cleaner and profiler designed to purge the insoluble salts and contaminants from the concrete surface, while creating a CSP of 1-4 without the need for shotblasting. Maxxon Commercial Profile increases porosity and reduces high alkalinity, creating a clean concrete surface that promotes bonding of Maxxon® primers and underlayments. Maxxon Commercial Profile is biodegradable and cleans up easily with water.

## Where to Use

### Application

Virtually all above-, below- and on-grade concrete-based construction applications.

### Subfloor

Interior old, new, compromised and chemically-abated concrete.

## Technical Characteristics

<b>VOCs</b>	0 g/L
<b>Color</b>	Translucent yellow liquid
<b>Dwell Time</b>	Approximately 2 hours to CSP 2
<b>Application Temperature</b>	40–90 °F (4.4–32 °C)
<b>pH</b>	2
<b>Coverage Per Application</b>	225–250 ft <sup>2</sup> /gal (5.5–6.1 m <sup>2</sup> /L) or 900–1000 ft <sup>2</sup> (84–93 m <sup>2</sup> )/pail
<b>Packaging</b>	4 gal (15.1 L) pail

## Features

- Cleans and profiles old, new, compromised and chemically-abated concrete to a CSP of 1–2 in approximately 2 hours and up to 3–4 with a second application
- Ideal for dust-free environments where mechanical profiling is not feasible
- Single component — ready to use
- Muriatic/HCl-free formulation
- Zero VOCs
- Easy to apply — hand-held spray application; no shotblasting required
- Biodegradable; self-neutralizing; water cleanup

Revised: 2026-03-18