

PrivacyShield® ABSC-25DES Designer Colors Barrier Septum Soundproofing Blanket



Description

Our PrivacyShield® ABSC-25DES Designer Colors Barrier Septum Soundproofing Blanket offers the benefits of both sound absorbers and noise barriers. Curtain panels are constructed with grommets across the top and hook and loop Velcro fasteners along the vertical edges. Available in rolls, standard panels sizes or custom panels. Add some color to your manufacturing and outdoor spaces!

Interior/Exterior Applications

- Free-hanging acoustic curtains in acoustical curtain enclosures
- Free-hanging noise barrier/sound absorber composite wall
- Divider partition between noise sources
- Line walls or ceiling of a mechanical room or building to reduce noise inside and outside of the room or building

Technical Characteristics

Size:	4' x 8' (nominal) Up to 4' x 25'
Thickness:	2" fiberglass (pre-sewn)
Substrate:	1 lb / ft ² mass loaded vinyl (MLV)
Finishes:	Exterior-grade covering stitched with TENARA® thread
Color:	12 colors available (see color chart)
Weight:	1.5 lbs / ft ²
Mounting Options:	Velcro® seals along vertical edges Stainless steel grommets across top
Fire Rating:	Class A per ASTM E84 Flame Spread: 25 Smoke Density: 350

Features

- Excellent acoustical performance
- Custom sizing
- Easy to install
- Durable, tear and abrasion-resistant
- Great UV and mildew resistance
- Highly water repellent
- Dimensionally stable; will not sag or stretch over time
- Bound along all edges and produced with grommets along top edge for hanging
- Other configurations available

Revised: 2025-04-30

PrivacyShield® ABSC-25DES Designer Colors Barrier Septum Soundproofing Blanket

Sound Absorbing Performance

Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
2"	0.16	0.47	0.44	0.87	0.56	0.30	0.60

Per ASTM C423

Sound Transmission Loss

Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	STC
2"	17	17	20	31	48	55	27

Per ASTM E90 & E413

Revised: 2025-04-30