

Whisperwave® Ribbon Sound Baffle



Description

The Whisperwave® Ribbon Sound Baffle allows you to unleash your creativity while reducing noise and reverberation. Add dimension and acoustical control right where you need it the most with Whisperwave® Ribbons. Suspend Whisperwave® Ribbons from ceiling-mounted cables using corkscrew hangers (sold separately). They may be hung as high or as low as necessary to avoid obstacles in the ceiling, work around HVAC or to achieve a particular design.

Made from Class 1 fire-rated melamine foam, Whisperwave® products are offered in standard and custom sizes and curve patterns. Whisperwave® products are lightweight and easy to install. Whisperwave® products are available in natural grey, natural white or may be HPC Coated to add color and additional protection.

Technical Characteristics

Size	1' x 4'
Thickness:	2"
Material:	Open-cell melamine foam core
Color:	Natural White Natural Grey HPC Coated Colors
Fire Rating:	Class 1 per ASTM E84 Meets UL 1717 (Willtec™ natural)
Mounting:	Corkscrew hangers (sold separately) are installed in the field for either wall-to-wall cable installation or ceiling-mounted cable installation.

Sound Absorbing Performance

Thickness	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	AVE
2"	1.0	5.4	10.8	16.3	18.7	24.0	12.7

Sabins per Baffle per ASTM C423-90A

Revised: 2025-04-30