

Whisperwave® Sound Baffle



Description

Whisperwave® Sound Baffle curved accent products allow you to unleash your creativity while reducing noise and reverberation. Whisperwave Sound Baffles create movement and are easily hung using a wall-to-wall system.

Ride the wave with Whisperwave.® Made from Class 1 fire-rated melamine foam, Whisperwave® products are safe for use in a wide range of applications.

Whisperwave® products are lightweight and easy to install. Whisperwave® products are available in natural white, natural grey or HPC Coated colors.

Technical Characteristics

Size	2' x 4'
Thickness:	2"
Material:	Open-cell melamine foam core
Color:	Natural White Natural Grey HPC Coated Colors
Fire Rating:	Class 1 per ASTM E84 Meets UL 1717 (Willtec™ natural)
Mounting:	Corkscrew hangers (sold separately) are installed in the field for either wall-to-wall cable installation or ceiling-mounted cable installation. Can be aligned in the same direction or arranged so that every other baffle is turned 90 degrees.

Sound Absorbing Performance

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	AVE
1.0	5.4	10.8	16.3	18.7	24.0	12.7

Sabins per Baffle per ASTM C423-90A

Revised: 2025-04-30